

ADHESIVA U

POWDER ADHESIVE FOR ALL TYPES OF WALLCOVERINGS

UPDATED DATA SHEET 13/10/2026

Product information

Powder adhesive suitable for all types of wallcoverings.

+ Does not stain
+ Strong initial tack
+ High coverage
+ Ready to use in just 5 minutes
+ Universal formula
+ Zero VOCs (volatile organic compounds)

Recommended Uses

- All types of wallcoverings
- Vinyl wallcoverings with paper or nonwoven backing
- Foam wallcoverings with paper or nonwoven backing
- Heavyweight vinyl wallcoverings with paper or nonwoven backing
- Nonwoven and duplex paper wallcoverings

Application Instructions

Surface Preparation

All substrates must be dry, absorbent, sound, and free of dust, paint, and oil. Any cracks or holes in the wall must be filled with our GLASTER lightweight filler. We always recommend using PRIMER AC to consolidate and prepare the surface and PRIMER SP, specially formulated to protect against mold and bacteria, on damp walls.

Product dilution

Mix the product with clean water according to the dilution table shown on the packaging

Product preparation

1. Stir the water vigorously.
2. Slowly pour the powder from the bag into the water while continuing to stir.
3. Allow the mixture to stand for 3 minutes.
4. Stir again.
5. The product is ready to use after 5 minute

Product Application

Apply the adhesive directly to the back of the wallcovering or to the wall, according to the wallcovering manufacturer’s instructions

ACM Italy S.r.l. Viale Enrico Mattei, 8 - 20010 Casorezzo (Milan)
+39 02 90361148 | info@acm-italy.com
www.acm-italy.com



ADHESIVA U

POWDER ADHESIVE FOR ALL TYPES OF WALLCOVERINGS

UPDATED DATA SHEET 13/10/2026

Cleaning
Immediately remove any excess adhesive from the seams using a clean, damp sponge. THE PRODUCT DOES NOT STAIN.

Product Technical Data

Physical form	Powder
Color	White
Solids content	100%
Customs code	3505 2030
Flammability	Nonflammable
Application temperature	+5°C +40°C
Waiting time	10-20 minutes
Open time	20-30 minutes
Complete drying	48 hours
Hazard classification	Nonhazardous
Frost resistance	Frost-resistant

Contraindications

Do not use the adhesive on nonabsorbent substrates. Do not install wallcoverings on damp or moldy walls or on inadequately prepared substrates. Any excess adhesive must be removed immediately using a clean, damp sponge.

Final provisions

Keep out of reach of children and pets. Dispose of waste in containers suitable for construction materials and in accordance with local regulations.

Storage

The product is guaranteed for 60 months from the date of manufacture when stored in its original, unopened packaging under standard conditions, between +5°C and +35°C (+41°F and +95°F). Store the product in a dry place, away from heat sources and direct sunlight.

Warnings

The information provided in this technical data sheet is based on decades of experience and is intended as general guidance. Users must determine

ACM Italy S.r.l. Viale Enrico Mattei, 8 - 20010 Casorezzo (Milan)
+39 02 90361148 | info@acm-italy.com
www.acm-italy.com



ADHESIVA U

POWDER ADHESIVE FOR ALL TYPES OF WALLCOVERINGS

UPDATED DATA SHEET 13/10/2026

whether the product is suitable for their specific application and assume responsibility for its use.

ACM Italy S.r.l. Viale Enrico Mattei, 8 - 20010 Casorezzo (Milan)
+39 02 90361148 | info@acm-italy.com
www.acm-italy.com