

ADHESIVA VOV

READY-TO-USE SPECIAL ADHESIVE FOR VINYL WALLCOVERING EDGES AND SEAMS

TECHNICAL DATA SHEET UPDATED 14/10/2026

Product Information	Ready-to-use specialty paste adhesive with exceptionally high tack, ideal for installing decorative borders over vinyl wallcoverings and other non-absorbent surfaces. It is particularly recommended for bonding the seams and edges of heavy vinyl wallcoverings. + Exceptional adhesive strength + Non-staining + High coverage
	• Decorative vinyl or paper borders • Perimeter finishes and profiles • Joints and edges with difficult adhesion
Coverage	Approximately 100–300 g/m², depending on the absorbency of the substrate and the application method used (brush or roller).
Application Instructions	**Substrate Preparation** All substrates must be dry, sound, and free of dust, paint, and oil. Fill any cracks and holes with our GLASTER lightweight filler. Level any surface irregularities with a standard gypsum-based skim coat. PRIMER AC is recommended to consolidate and prepare the substrate. For damp walls, use PRIMER SP, specifically formulated to help prevent mold and bacterial growth.
	Product preparation The product is ready to use.
	Product application Apply a single coat of adhesive using a brush or roller. If applying the adhesive to both the wall and the border, install the border immediately, before a surface film forms.
	Cleaning Consult the wallcovering manufacturer’s cleaning instructions before proceeding. The product is non-staining.

ACM Italy S.r.l. Viale Enrico Mattei, 8 - 20010 Casorezzo (Milan) - Italy
+39 02 90361148 | info@acm-italy.com
www.acm-italy.com



ADHESIVA VOV

READY-TO-USE SPECIAL ADHESIVE FOR VINYL WALLCOVERING EDGES AND SEAMS

TECHNICAL DATA SHEET UPDATED 14/10/2026

Technical Data	Physical state	Creamy paste
	pH	7
	Viscosity	8,500 cP
	VOC content	< 0.005 mg/m³
	Solids content	Approx. 45%
	Customs code	3505 2010
	Application temperature	+5 °C to +40 °C
	Waiting time	0–15 minutes
	Open time	Approx. 30 minutes
	Complete drying time	48 hours
	Flammability	Non-flammable

Warnings	Do not use on wet walls or surfaces affected by mold. Remove any adhesive residue immediately with a damp sponge..
Storage	The product is guaranteed for 24 months from the date of manufacture when stored in its original packaging under normal storage conditions (+5°C to +35°C / +41°F to +95°F). Store the product in a dry place, away from heat sources and direct sunlight.
Disposal	Keep out of reach of children and pets. Dispose of waste in designated construction-waste containers.
Disclaimer	The information provided in this Technical Data Sheet is based on our extensive experience and is intended as general guidance only. Users are responsible for determining whether the product is suitable for the intended application and for ensuring its proper use.

ACM Italy S.r.l. Viale Enrico Mattei, 8 - 20010 Casorezzo (Milan) - Italy
+39 02 90361148 | info@acm-italy.com
www.acm-italy.com