

TEXRECO CS 1000

CLAY WALLCOVERING ADHESIVE
EXTRA-STRENGTH ADHESIVE

DATA SHEET UPDATED 07/10/2026

Product information

Clay Wallcovering Adhesive for medium to heavyweight wallcoverings of wallcoverings. Designed to be easily applied with a spatula or roller. Ideal for applications with wall coverings that require low humidity. Suitable for absorbent and non-absorbent surfaces.

+ Exceptional adhesive strength
+ Does not stain
+ High solids
+ Maximum wet tack
+ Very Low V.O.C. (Volatile Organic Compounds)

Recommended uses

- Type II-III wallcoverings
- Medium to heavyweight wallcoverings
- Vinyl contract wall coverings with fabric or non-woven backing with a weight up to 1 kg/m2
- Wallcoverings with cotton fabric support
- Difficult application

Coverage

Approximately 200 square feet per gallon, depending on the porosity of the substrate.

Application instructions

Surface preparation
All surfaces must be dry, absorbent, strong, and free of dust, paints, or oils. Any cracks or holes in the wall must be filled with our extra-light stucco GLASTER. We always recommend using our Primer STO-B if there are mildew stains on the wall, our Primer STO-R like promoter for non-porous surfaces and our Primer STO-SP to fix and prevent mouldings on the walls.

Product preparation
TEXRECO CS 1000 is a ready-to-use product. Do not dilute.

Application
Apply the adhesive on the back of the wallpaper or on the wall according to manufacturer's instructions.

Cleaning
Clean possible spills with a damp sponge. Additional effort may be required for embossed or textured vinyls. THE PRODUCT DOES NOT STAIN

ACM Italy S.r.l. Viale Enrico Mattei, 8 - 20010 Casorezzo (Milano)
+39 02 90361148 | info@acm-italy.com
www.acm-italy.com

TEXRECO CS 1000

CLAY WALLCOVERING ADHESIVE
EXTRA-STRENGTH ADHESIVE

DATA SHEET UPDATED 07/10/2026

Technical product data	Base	Clay
	Appearance and colour	beige cream
	PH	7.5
	Viscosity	100000 cps
	VOC	< 2 µg/m^3
	Solids percentage	> 70%
	Customs code	3505 2010
	Application temperature	+5°C +40°C
	Waiting Time	10-15 min
	Open Time	30-40 min
	Drying Time	48 hours
	Non-Flammable product	
	Keep free from frost	

Warning

TEXRECO CS 1000 is not suitable on imperfect prepared substrates or humid walls. Spillage of the adhesive should be removed immediately with a damp sponge.
Keep out of reach of children and pets. Discharge the waste in special containers for building materials.

Storage

The product is guaranteed in its original packaging, in standard conditions (+5 °C a +35 °C or +41 °F to +95 °F), for 24 months from the date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

Disclaimer

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.

ACM Italy S.r.l. Viale Enrico Mattei, 8 - 20010 Casorezzo (Milano)
+39 02 90361148 | info@acm-italy.com
www.acm-italy.com